

Gas filter, process for producing a gas filter and use
of this gas filter

5 A gas filter, a process for producing a gas filter and
use of this gas filter are claimed.

10 Air pollution is known to present a serious problem in
many parts of the world. Depending on composition, the
pollution can lead to health problems among the human
population. Furthermore, the air pollution results in
not inconsiderable economic loss. The air pollution can
be in the form of gases or of liquids dispersed very
finely in the air or in the form of tiny solid par-
ticles present in the air. The solid particles which
15 may be present in the air and have been and are classi-
fied as carcinogenic include soot, especially soot
(particulates) which gets into the air via the exhaust
gases of diesel vehicles.

20 In many nations, regulations to regulate the maximum
permissible emission of particulates from motor
vehicles have been put in force.

25 Various methods and apparatus have already been
developed for treating solids-containing gases.

US 4872889 and US 4948493 claim ceramic filter systems
which are able to filter soot or solid particles from
the exhaust gases of diesel-powered vehicles.

30 A problem with these methods and apparatus is that the
solid particles block the filter relatively quickly and
the filters thus have to be replaced or regenerated at
short intervals.

35 To regenerate blocked filters, there have been pro-
posals for methods which burn the solids blocking the
pores of the filter in motor vehicles by additional
combustion of fuel. The disadvantage of these methods

09956945 092104
101260 51695660

is that regeneration leads to an increased fuel consumption. In addition, the deep action of this method is only weak, so that blockages caused by particles in the filter cannot be remedied.

5

More recently, methods and apparatus which remove filtered-out solids from the filter by heating to 600°C have been developed.

10 According to DE 3800723, additional heating wires are used for heating the filter.

EP 0275372 uses heating elements comprising wire, expanded metal or perforated foils for heating the
15 filter.

GB 2193656 teaches a method and an apparatus which make use of wires between which a current flows when a conductive bridge of deposited soot forms.

20

US 5202548 describes a filter which can be baked out by application of a voltage since it is equipped with electrically conductive honeycomb structures.

US 5246672 teaches the use of woven wire meshes and
25 US 5254840 teaches the use of a combination of metallic and ceramic honeycombs.

The filter materials used in the abovementioned methods or apparatus have relatively small surface areas and
30 thus either a low filter action or, when the pores are made smaller to increase the filter action, a small gas throughput. If the surface area is large due to the use of porous materials, the pores become blocked very quickly. Filtering relatively large amounts of gas
35 requires the use of large, relatively cumbersome gas filters which restricts the possible uses of such gas filters.

It is therefore an object of the present invention to find an economical process for producing a gas filter which, despite a small size, is able to filter large amounts of gas and which can be regenerated in a simple manner.

It has surprisingly been found that a gas filter which comprises a material-permeable composite material based on at least one open-structured and material-permeable support and having on at least one side of the support and in the interior of the support at least one inorganic component which comprises essentially at least one compound of a metal, a semimetal or a mixed metal with at least one element of main groups III to VII is able, even when small in size, to filter large amounts of gas and can be regenerated in a simple manner.

The present invention accordingly provides a regenerable gas filter for filtering gases which comprises a composite material based on at least one open-structured and material-permeable support and having on at least one side of the support and in the interior of the support at least one inorganic component which comprises essentially at least one compound of a metal, a semimetal or a mixed metal with at least one element of main groups III to VII.

The present invention likewise provides a regenerable gas filter which comprises a composite material which is obtainable by application of a suspension which comprises at least one inorganic component comprising a compound of at least one metal, a semimetal or a mixed metal with at least one element of main groups III to VII and a sol to an open-structured and material-permeable support and by subsequent heating at least once during which the suspension comprising at least one inorganic component is solidified on or in or on and in the support.

5 The present invention also provides a process for producing a gas filter as claimed in any of claims 1 to 40, which comprises producing a material-permeable composite material by applying, in and on at least one open-structured and material-permeable support, at least one suspension which comprises at least one inorganic component comprising at least one compound of at least one metal, a semimetal or a mixed metal with
10 at least one of the elements of main groups III to VII and a sol and by solidifying the suspension on or in or on and in the support material by subsequent heating at least once.

15 The present invention likewise provides for the use of a gas filter as claimed in any of claims 1 to 40 for cleaning waste or feed gases.

20 For the purposes of the present invention, material-permeable means that materials which have this property are permeable to at least a gas, a liquid or a solid. The permeability is dependent on the size of the pores, mesh openings or holes which these materials have.

25 The gas filter of the invention can be used for the filtration of any waste and feed gases from which, for example, solid particles are to be removed. The gases to be filtered can also comprise vapor or droplets of liquid. The advantage of the gas filter of the invention is that, as a result of the use of an electrically
30 conductive support material in the composite material, the latter can be baked out in a simple manner by application of a voltage and thus be regenerated. If the composite material comprises catalytically active materials, this heating only has to be carried out once
35 if the decomposition of the thermally decomposable liquid droplets or solid particles is, in the case of a sufficiently hot filter, catalyzed by the catalytically active materials and thus proceeds swiftly. As a

000005 000004
000003 000002
000001 000000

result, advantageously, a virtually constant amount of gas can pass through the filter since blocking of the filter by materials which are not thermally decomposable increases only very slowly.

5

A further advantage of the gas filter of the invention is that the novel composite material or gas filter can, due to the fact that it is bendable, be rolled or folded and the filter-active surface area of the filter can be very large in a small volume.

10

The gas filter of the invention is described below by way of example without being restricted thereby.

15 The regenerable gas filter of the invention for the filtration of gases comprises at least one composite material based on at least one open-structured and material-permeable support and having on at least one surface of the support and in the interior of the support at least one inorganic component which comprises essentially at least one compound of a metal, a semimetal or a mixed metal with at least one element of main groups III to VII. For the purposes of the present invention, interior of a support means, for example, hollow spaces or pores in a support.

20

25

According to the invention, the regenerable gas filter comprises a composite material which is obtained by application of a suspension which comprises at least one inorganic component comprising a compound of at least one metal, a semimetal or a mixed metal with at least one element of main groups III to VII and a sol to an open-structured and material-permeable support and by heating at least once during which the suspension comprising at least one inorganic component is solidified on or in or else on and in the support.

30

35

According to the invention, the composite material or gas filter can be permeable to gases, solids or

09956915 092101
TOT260 51695660

liquids, in particular to particles having a size of from 0.5 nm to 10 μm .

5 A support having intermediate spaces having a size of from 50 to 500 μm can advantageously be present in the composite material of the gas filter. This support can comprise woven or felted fibers, expanded metal or sintered metal. The support preferably comprises at least one at least partially electrically conductive
10 material.

The intermediate spaces can be pores, mesh openings, holes, crystal lattice interstices or voids. The support can comprise at least one material selected from
15 the group consisting of carbon, metals, alloys, glass, ceramics, minerals, plastics, amorphous substances, natural products, composite materials or at least one combination of these materials. The supports which can comprise the abovementioned materials can have been
20 modified by a chemical, thermal or mechanical treatment method or a combination of treatment methods. Preferably, the composite material comprises a support comprising at least one metal, a natural fiber or a plastic which has been modified by at least one
25 mechanical forming technique or treatment method, e.g. drawing, swaging, fulling, rolling, stretching or forging. Very particularly preferably, the composite material comprises at least one support comprising at least woven, bonded, felted or ceramically bound fibers
30 or at least sintered or bonded shaped bodies, spheres or particles. In a further, preferred embodiment, a perforated support can be used. Material-permeable supports can also be ones which become or have been made material-permeable by laser treatment or ion beam
35 treatment.

It can be advantageous for the support to comprise fibers of at least one material selected from the group consisting of carbon, metals, alloys, ceramics, glass, minerals, plastics, amorphous substances, composite

materials and natural products or fibers of at least one combination of these materials, e.g. asbestos, glass fibers, rock wool fibers, carbon fibers, metal wires, steel wires, polyamide fibers, coconut fibers or coated fibers. Preference is given to using supports which comprise at least woven fibers of metal or alloys. Wires can also serve as metal fibers. The composite material very particularly preferably comprises a support comprising at least one woven mesh of steel or stainless steel, e.g. woven meshes produced from steel wires, steel fibers, stainless steel wires or stainless steel fibers by weaving, which preferably has a mesh opening of from 5 to 500 μm , particularly preferably mesh openings of from 50 to 500 μm and very particularly preferably mesh openings of from 70 to 120 μm .

The support of the composite material can, however, also comprise at least one expanded metal having a pore size of from 5 to 500 μm . According to the invention, the support can also comprise at least one granular, sintered metal, a sintered glass or a metal nonwoven having a pore width of from 0.1 μm to 500 μm , preferably from 3 to 60 μm .

According to the invention, the composite material preferably comprises a support comprising at least aluminum, silicon, cobalt, manganese, zinc, vanadium, molybdenum, indium, lead, bismuth, silver, gold, nickel, copper, iron, titanium, platinum, stainless steel, steel, brass, an alloy of these materials or a material coated with Au, Ag, Pb, Ti, Ni, Cr, Pt, Pd, Rh, Ru and/or Ti.

The inorganic component present in the composite material or gas filter can comprise at least one compound of at least one metal, semimetal or mixed metal with at least one element of main groups III to VII of the Periodic Table or at least one mixture of these

compounds. Here, the compounds of the metals, semi-
metals or mixed metals can comprise at least elements
of the transition series and main groups III to V or at
least elements of the transition series or main groups
5 III to V, with these compounds having a particle size
of from 0.001 to 25 μm . The inorganic component prefer-
ably comprises at least one compound of an element of
main groups III to VIII or at least one element of main
groups III to V with at least one of the elements Te,
10 Se, S, O, Sb, As, P, N, Ge, Si, C, Ga, Al or B or at
least one compound of an element of main groups III to
VIII and at least one element of main groups III to V
with at least one of the elements Te, Se, S, O, Sb, As,
P, N, Ge, Si, C, Ga, Al or B or a mixture of these
15 compounds. Particularly preferably, the inorganic com-
ponent comprises at least one compound of at least one
of the elements Sc, Y, Ti, Zr, V, Nb, Cr, Mo, W, Mn,
Fe, Co, B, Al, Ga, In, Tl, Si, Ge, Sn, Pb, Sb or Bi
with at least one of the elements Te, Se, S, O, Sb, As,
20 P, N, C, Si, Ge or Ga, e.g. TiO_2 , Al_2O_3 , SiO_2 , ZrO_2 , Y_2O_3 ,
BC, SiC, Fe_3O_4 , SiN, SiP, nitrides, sulfates,
phosphides, silicides, spinels or yttrium-aluminum
garnet or one of these abovementioned elements itself.
The inorganic component can also comprise alumino-
25 silicates, aluminum phosphates, zeolites or partially
exchanged zeolites such as ZSM-5, Na-ZSM-5 or Fe-ZSM-5
or amorphous microporous mixed oxides which may contain
up to 20% of non-hydrolyzable organic compounds, e.g.
vanadium oxide-silicon oxide glass or aluminum oxide-
30 silicon oxide-methylsilicon sesquioxide glasses.

Preferably, at least one inorganic component is present
as a particle size fraction having a particle size of
from 1 to 250 nm or having a particle size of from 260
35 to 10,000 nm.

It can be advantageous for the composite material to
comprise at least two particle size fractions of at
least one inorganic component. The particle size ratio

09956915 092101
101250 51695660

of the particle size fractions in the composite material is from 1:1 to 1:10,000, preferably from 1:1 to 1:100. The composite material particularly preferably comprises at least one particle size fraction
5 having an average particle size of from 0.3 to 3 μm .

The ratio of the amounts of the particle size fractions in the composite material is preferably from 0.01:1 to 1:0.01.

The material permeability of the composite material can
10 be limited to particles having a particular maximum size by means of the particle size of the inorganic component used. It can be advantageous for the composite material to have pores which are permeable to particles having a maximum size of from 0.1 to 10 μm ,
15 particularly preferably a maximum size of from 0.2 to 1.5 μm .

The suspension which comprises at least one inorganic component and by means of which the composite material
20 of the invention can be obtained can comprise at least one liquid selected from the group consisting of water, alcohol and acid or a combination of these liquids.

In a further particular embodiment of the gas filter of
25 the invention, the composite material comprises at least one catalytically active component. The catalytically active component can be identical to the inorganic component. This applies particularly when the inorganic component has catalytically active centers on
30 the surface.

The catalytically active component present in the composite material is preferably at least one inorganic material, at least one metal or at least one organo-
35 metallic compound which has catalytically active centers on its surface. The catalytic component present in the composite material is particularly preferably a zeolite such as ZSM-5, Fe-ZSM-5, silicalite or an amorphous microporous mixed oxide as described, for

0095915 092101
101260 5169560

example, in DE 195 45 042 and/or DE 195 06 842, e.g. vanadium oxide-silicon oxide glass or aluminum oxide-silicon oxide-methylsilicon-sesquioxide glasses.

- 5 The composite material can, however, also comprise at least one oxide of at least one of the elements Mo, Sn, Zn, V, Mn, Fe, Co, Ni, As, Sb, Pb, Bi, Ru, Re, Cr, W, Nb, Hf, La, Ce, Gd, Ga, In, Tl, Ag, Cu, Li, K, Na, Be, Mg, Ca, Sr and Ba as catalytically active component.

10

In a particular embodiment of the material-permeable composite material, this comprises at least titanium suboxide as catalytically active component.

- 15 It can likewise be advantageous for the composite material to comprise, as catalytically active component, at least one metal compound selected from among the compounds of the metals Pt, Rh, Ru, Ir, Au, Ag, Os, Re, Cu, Ni, Pd and Co, or at least one metal selected
20 from among the metals Pt, Rh, Ru, Ir, Au, Ag, Os, Re, Cu, Ni, Pd and Co.

- Particularly preferred catalytic components are, for example, noble metals, noble metal compounds or
25 materials coated with noble metal particles. The addition of the catalytically active component makes it possible to achieve a situation where the filter becomes blocked more slowly after heating once due to catalytic decomposition of thermally decomposable
30 solids or liquids, since only particles which cannot be destroyed thermally block the filter. This particular embodiment enables the operating life of the filter of the invention to be increased considerably.

- 35 In a particularly preferred embodiment of the gas filter or composite material of the invention, this can be made bendable without destruction of the inorganic component solidified in the interior of the support and on the support. The composite material of the invention

0095915 092101
T01260 5155560

[illegible]

In one variant of the gas filter of the invention, thermally decomposable or sublimable or vaporizable solids or liquids which have been filtered from a
15 filtered gas and block the pores of the composite material, e.g. soot or hydrocarbon particles, can be removed from the gas filter by baking out the gas filter by application of a voltage to the support of the composite material. Depending on the selected
20 support material, preferably a support material having a low electrical resistance, the filter can be heated using a low voltage as is customary, for example, in motor vehicles, e.g. 12 or 24 V.

The process of the invention for producing the gas filter of the invention is described below, without
35 being restricted thereto.

The gas filter of the invention can be produced by producing a material-permeable composite material by applying, in and/or on at least one open-structured and

material-permeable support, at least one suspension which comprises at least one inorganic component comprising at least one compound of at least one metal, a semimetal or a mixed metal with at least one of the elements of main groups III to VII and a sol and by solidifying the suspension on or in or on and in the support material by subsequent heating at least once.

When carrying out the process of the invention, it can be advantageous to apply the suspension on and in or else on or in at least one support by printing, pressing-on, pressing-in, rolling-on, doctor blade coating, painting-on, dipping, spraying or casting.

The open-structured and material-permeable support can comprise a material selected from the group consisting of carbon, metals, alloys, ceramics, glass, minerals, plastics, amorphous substances, natural products, composite materials or at least one combination of these materials. The preferred support is a woven stainless steel or steel mesh.

The suspension used, which comprises at least one inorganic component and at least one metal oxide sol, at least one semimetal oxide sol or at least one mixed metal oxide sol or a mixture of these sols, can be produced by suspending at least one inorganic component in at least one of these sols. It can be advantageous for the suspension to comprise at least one catalytically active component. The catalytically active component can be identical to the inorganic component.

The sols are obtained by hydrolyzing at least one metal compound, at least one semimetal compound or at least one mixed metal compound using a liquid, a gas or a solid. It can be advantageous for the liquid used for hydrolyzing the compound to be hydrolyzed to be water, alcohol or an acid or a combination of these liquids or the solid used to be ice or the gas used to be water

0995615 092104
101260 5159560

vapor. It can likewise be advantageous for the compound to be hydrolyzed to be added prior to the hydrolysis to at least one alcohol or at least one acid or a combination of these liquids. As compound to be hydrolyzed, preference is given to hydrolyzing at least one metal nitrate, a metal chloride, a metal carbonate, a metal alkoxide compound or at least one semimetal alkoxide compound, particularly preferably at least one metal alkoxide compound, a metal nitrate, a metal chloride, a metal carbonate or at least one semimetal alkoxide compound selected from among the compounds of the elements Ti, Zr, Al, Si, Sn, Ce and Y or the lanthanides and actinides, e.g. zirconium alkoxide, silicon alkoxide or titanium alkoxide compounds, e.g. titanium isopropoxide, silicon alkoxides, zirconium alkoxides, or a metal nitrate such as zirconium nitrate.

It can be advantageous to carry out the hydrolysis of the compounds to be hydrolyzed using at least half the molar ratio of water, water vapor or ice, based on the hydrolyzable group, of the hydrolyzable compound.

The hydrolyzed compound can be peptized by treatment with at least one organic or inorganic acid, preferably a 10-60 strength organic or inorganic acid, particularly preferably a mineral acid selected from the group consisting of sulfuric acid, hydrochloric acid, perchloric acid, phosphoric acid and nitric acid and mixtures of these acids.

It is possible to use not only sols which have been prepared as described above but also commercial sols such as titanium nitrate sol, zirconium nitrate sol or silica sol.

It can be advantageous if at least one inorganic component having a particle size of from 1 to 10,000 nm is suspended in at least one sol. Preferably, an inorganic component comprising at least one compound selected from among metal compounds, semimetal compounds, mixed

It can likewise be advantageous for at least one catalytically active component having a particle size of from 1 to 10,000 nm to be suspended in a sol. Preferably, at least one catalytically active component comprising at least one compound selected from among metal compounds, semimetal compounds, mixed metal compounds and metal mixed compounds with at least one of the elements of main groups III to VII or organic compounds, or at least one mixture of these compounds, is suspended. Particularly preferably, at least one catalytically active component comprising at least one compound selected from among aluminosilicates, aluminum phosphates, zeolites or partially exchanged zeolites,

e.g. ZSM-5, Na-ZSM-5 or Fe-ZSM-5, and amorphous microporous mixed oxides which may contain up to 20 of non-hydrolyzable organic compounds, e.g. vanadium oxide-silicon oxide glass or aluminum oxide-silicon oxide-methylsilicon sesquioxide glasses, is suspended.

The proportion by mass of the suspended components is preferably from 0.1 to 500 times that of the hydrolyzed compound used.

10

Appropriate selection of the particle size of the suspended compounds as a function of the size of the pores, holes or intermediate spaces of the open-structured material-permeable support, but also the layer thickness of the composite material of the invention and the sol-solvent-metal oxide ratio, enable the freedom from cracks of the gas filter of the invention or the composite material to be optimized.

15

20 When using a woven mesh having a mesh opening of, for example, 100 μm , it is possible to increase the freedom from cracks by using, preferably, suspensions which comprise a suspended compound having a particle size of at least 0.7 μm . In general, the ratio of particle size to mesh opening or pore size should be from 1:1000 to 50:1000. The composite material of the invention preferably has a thickness of from 5 to 1000 μm , particularly preferably from 50 to 150 μm . The suspension comprising sol and compounds to be suspended preferably has a weight ratio of sol to compounds to be suspended of from 0.1:100 to 100:0.1, preferably from 0.1:10 to 10:0.1.

25

30

According to the invention, the suspension present on or in or else on and in the support can be solidified by heating the composite at from 50 to 1000°C. In a particular variant, the composite is subjected to a temperature of from 50 to 100°C for from 10 minutes to 5 hours. In a further particular variant, the composite

35

	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349	2350	2351	2352	2353	2354	2355	2356	2357	2358	2359	2360	2361	2362	2363	2364	2365	2366	2367	2368	2369	2370	2371	2372	2373	2374	2375	2376	2377	2378	2379	2380	2381	2382	2383	2384	2385	2386	2387	2388	2389	2390	2391	2392	2393	2394	2395	2396	2397	2398	2399	2400	2401	2402	2403	2404	2405	2406	2407	2408	2409	2410	2411	2412	2413	2414	2415	2416	2417	2418	2419	2420	2421	2422	2
--	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	---

35

In a further, particular embodiment of the process of the invention it can be advantageous to apply a ceramic or inorganic layer to a support which may be a composite material or a composite material produced by

the process of the invention. This can be carried out, for example, by laminating a green (unsintered) ceramic layer or an inorganic layer which is, for example, present on an auxiliary film onto the support or by
5 treating the composite material with a further suspension as described above. This composite can be strengthened by heating, e.g. by means of infrared radiation or a furnace.

10 The green ceramic layer used preferably comprises nanocrystalline powder of at least one semimetal oxide or metal oxide such as aluminum oxide, titanium dioxide or zirconium dioxide. The green layer can also comprise an organic binder.

15 The use of a green ceramic layer makes it readily possible to provide the composite material of the invention with an additional ceramic layer which, depending on the size of the nanocrystalline powder
20 used, restricts the material permeability of the composite material produced in this way to very small particles.

The green layer preferably comprises nanocrystalline
25 powder having a particle size of from 1 to 1000 nm. If nanocrystalline powder having particle sizes of from 1 to 10 nm is used, the composite material of the invention to which an additional ceramic layer has been applied has a material permeability for particles
30 having a size which corresponds to that of the particle size of the powder used. If nanocrystalline powder having a size above 10 nm is used, the ceramic layer is permeable to particles which are half the size of the particles of the nanocrystalline powder used.

35 The application according to the invention of at least one further inorganic layer or ceramic layer gives a composite material of the invention which has a pore gradient. In addition, multiple application of a layer

0936915-093401
101260 5169560

The crack insensitivity of composite materials having large mesh openings or pore sizes can also be improved by applying suspensions which comprise at least two suspended compounds to the support. As compounds to be suspended, preference is given to using compounds which have a particle size ratio of from 1:1 to 1:10, particularly preferably from 1:1.5 to 1:2.5. The proportion by weight of the particle size fraction having the smaller particle size should not exceed a proportion of at most 50%, preferably 20% and very particularly preferably 10%, of the total weight of the particle size fractions used.

Despite the application of an additional ceramic layer or inorganic layer, which may comprise catalytically active components, to the support, the composite material of the invention can be bendable.

The gas filter of the invention or the composite material can also be produced by laying a support, which may, for example, be a composite material or

another suitable support material, onto a second support which may consist of the same material as the first support or a different material or of two supports having a different material permeability or porosity. A spacer, a drainage material or another material suitable for conducting away materials, e.g. a composite fabric, can be laid between the two support materials. The edges of the two supports are joined together, for example by soldering, welding or adhesive bonding. Adhesive bonding can be carried out using commercial adhesives or adhesive tape. The suspension can be applied in the manner described above to the composite support prepared in this way.

In a particularly preferred embodiment, the superposed supports between which at least one spacer, a drainage material or the like may be arranged can be rolled up before or after, preferably after, the joining of the edges of the supports. The spacing between two composite supports which become juxtaposed on rolling-up can be influenced by use of thick or thin adhesive tapes for joining the edges of the supports. A suspension as described above can be applied to such rolled-up composite supports by, for example, dipping into a suspension. The composite support can be freed of excess suspension by means of compressed air after dipping. The suspension applied to the composite support can be solidified as described above. A gas filter or composite material produced in this way can be used as gas filter in a rolled module.

In a further particular embodiment of the process of the invention, the composite support mentioned can also be produced by unrolling two supports and, if provided, at least one spacer from individual rolls and then laying them on top of one another. The edges of the supports can again be joined by soldering, welding, adhesive bonding or by other suitable methods of joining flat bodies. The suspension can then be applied to the composite support produced in this way. The

[illegible]

20

35

It can be advantageous to use the composite material as support for the production of a gas filter or composite material according to the invention.

In a particular embodiment of the process of the invention, it is possible, after solidification of the suspension or ceramic or inorganic layer on and/or in the support material, to treat the dried and strengthened gas filter or composite material with a solution comprising at least one metal compound, preferably a metal salt such as RhCl_3 . The treatment can comprise, for example, spraying, painting or rolling the solution comprising a metal compound onto the composite material or, for example, dipping the composite material into a solution comprising a metal compound. The gas filter or composite material which has been treated in this way is dried by heating. Heating can be carried out as indicated above. The metal compound which is present in and on or in or on the composite material after application and drying of the solution is reduced to the metal.

It can be advantageous to reduce a metal compound present in and/or on the composite material to the metal using a reducing agent, preferably a borohydride, very particularly preferably NaBH_4 , LiBH_4 , NaBMe_3 or KBPrH .

It can likewise be advantageous to reduce a metal compound present on or in or else on and in the composite material to the metal by using the composite material as electrode in an electrolysis.

Catalytically active metals can also be applied in and/or on the gas filter or composite material by using a composite material without a catalytically active component as electrode in the electrolysis of a solution comprising a noble metal salt. Here, it is necessary for the composite material to comprise at least TiO_2 as an inorganic component and at least one partially electrically conductive support. On application of a voltage of, for example, from 2 to 3 volt, the composite material becomes electrically conductive

due to formation of titanium suboxide, which is electrically conductive. As a result of the electrolysis, catalytically active noble metal, preferably in the form of very fine particles, deposits in and/or on the composite material or gas filter.

This makes it possible to produce gas filters which comprise metals and/or noble metals as catalytic components.

10

It is also possible to use the gas filter or composite material of the invention as support for producing a gas filter according to the invention.

15 In a particular variant for producing the gas filter of the invention, at least one material-permeable composite material is introduced, preferably rolled or folded, into a container having at least two openings.

20 The composite material is preferably fixed in the container, preferably by welding, soldering or adhesive bonding, so that a gas flowing through the filter has to pass through the composite material at least once. The support in the composite material of the gas filter
25 is preferably connected to at least one power lead.

It can be advantageous to combine preferred embodiments of the process of the invention with at least one further preferred embodiment of the process of the invention. It may likewise be advantageous to combine preferred embodiments of the gas filter of the invention with at least one further preferred embodiment of the gas filter of the invention. With knowledge of the present invention, a person skilled in the art will be
30 able to see further embodiments of the process of the invention, the gas filter of the invention and/or further possible uses of the process of the invention or the gas filter of the invention.
35

The gas filter of the invention can be used for cleaning gases, in particular waste gases or feed gases, and very particularly preferably gases containing at least one solid.

5

The gas filters of the invention are preferably used for cleaning waste gases from power stations or for cleaning the exhaust gases from vehicles driven by internal combustion engines. The gas filter of the invention is very particularly preferably used for cleaning the exhaust gases from vehicles driven by diesel engines.

The following examples describe the process of the invention for producing a gas filter according to the invention, without the process being restricted to these examples.

Example 1

20

A suspension comprising 25 g of zirconium isopropoxide was hydrolyzed with 20 g of water. The resulting precipitate was subsequently treated with about 40 g of 25% strength nitric acid and, after the precipitate had dissolved completely, 60 g of aluminum oxide (Al6SG from Alcoa) were added. This suspension was stirred until all agglomerates had completely dissolved and was applied in a thickness of 60 μm to a square-weave mesh of stainless steel having a mesh opening of 70 μm . This composite was exposed to air at 450°C for 3 seconds and was dried and solidified in this way.

The composite material obtained in this way was used for gas filtration. The present composite material is suitable, when installed in a gas filter, for filtering exhaust gases from diesel engines, since solid particles having a size of upward from 0.25 μm are selectively retained.

0095615 02401
"02460" 5165560

10

10

15

25

35

of the invention, energy does not have to be consumed continually for regeneration of the filter, but it is sufficient for the gas filter to be heated at least once during the start-up or running-up phase. Once the
5 reaction in and on the filter is proceeding, the energy liberated in the destruction of the solid particles generates the high temperatures necessary for regeneration of the filter.

0926915 092404
FOI260 9169366